

IS 380

Headphones | Wireless Hi-fi Headphones

Cat. No. 004449

General Description

The IS 380 system consists of the TI 380 infra-red transmitter and HDI 380 hi-fi stereo headphones. High sound quality is matched by excellent comfort for the wearer and modern styling. The transmitter can be connected to the headphone socket of any sound source.



Technical Data – HDI 380 Headphones

Modulation.....	FM
Carrier frequencies	2.3/2.8 MHz
Frequency response	20 – 19,000 Hz
THD	< 1 %
Signal-to-noise ratio	typ. 46 dB(A)
Operating time	approx. 4 h per accupack
Max. SPL	approx. 106 dB
Weight	approx. 190 g

Technical Data – TI 380 Transmitter

Modulation.....	FM
Carrier frequencies	2.3/2.8 MHz
THD	< 1 %
Signal-to-noise ratio	typ. 46 dB(A)
Power consumption	3 VA
Weight	approx. 190 g
Connector	3.5 mm stereo mini jack plug with adaptor to 1/4" (6.3 mm) stereo jack plug

Features

- Headphones extremely comfortable to wear
- Can be connected to televisions, hi-fi systems, CD players and DAT or MD recorders
- High sound quality
- Delivery includes: 1 pair of HDI 380 headphones, 1 BA 151 accupack, 1 TI 380 transmitter, 1 plug-in mains unit, 1 audio connection cable with 3.5 mm/1/4" jack plug

Recommended Accessories

- BA 151 accupack Cat. No. 004146
- HDI 380 supplementary headphones Cat. No. 004571

Replacement Parts

- Ear pads (1 pair) Cat. No. 070831
- Adaptor cable for connection to SCART socket Cat. No. 047874

Product Variants

- IS 380-120: as IS 380, but with USA plug-in mains unit Cat. No. 004450
- IS 380-UK: as IS 380, but with UK plug-in mains unit Cat. No. 004451

HDI 380			TI 380	
20-19,000 Hz	< 1 %	190 g	2.3/2.8 MHz	3.5/6.3 mm